

Celebrity® X6

The Celebrity® X6 comes fully loaded with standard features that make it as easy to enjoy as it is to use. A standard deluxe seat and adjustable delta tiller with wraparound handles make the Celebrity X6 a perfect blend of comfort, convenience and performance.



Celebrity® X6
4-wheel
Shown in Silver

Pride
Mobility Products Ltd.

Unit 106, Heyford Park, Camp Road
Upper Heyford, Oxfordshire, OX25 5HA
Tel: 44 1869 233 100
Fax: 44 1869 233 400



www.pridemobility.com

Celebrity X6

Specifications:

WEIGHT CAPACITY:	159kg (25 STONE)
MAXIMUM SPEED:	Up to 9.5 km/h (6.25 mph)
GROUND CLEARANCE:	9 cm (3.5")
TURNING RADIUS:	150 cm (59")
LENGTH:	119 cm (46.75")
WIDTH:	61 cm (24")
FRONT TYRES:	9 cm x 25 cm (3.5" x 10")
REAR TYRES:	10 cm x 25 cm (4" x 10")
ANTI-TIPS:	Rear
STANDARD SEAT:	Deluxe seat with headrest
SUSPENSION:	Front and rear
BATTERY CHARGER:	Off-board
PER-CHARGE RANGE:**	Up to 45 km (28 miles)
BATTERIES:	2 x 12V, 30 amp
BATTERY WEIGHT:	11 kg (24.5 lbs.) each
TOTAL w/o BATTERY	
PACKS:	68.5 kg (151 lbs.)
HEAVIEST PIECE	
WHEN DISASSEMBLED:	30 kg (66 lbs.)

Features:

- State-of-the-art rear suspension
- Top speed of up to 9.5 km/h (6.25 mph)
- Maximum weight capacity of 159 kg (25 Stone)
- Ultra-simple, auto-latching lockup for quick disassembly/reassembly
- Easily accessible tie down points (for transport of unoccupied scooter)
- Front basket and rearview mirror standard
- Tight turning radius of 150 cm (59")
- Includes standard angle-adjustable light
- Front frame-mounted seat post for optimal stability
- High visibility reflectors
- Microprocessor-based controller
- Tiller rotation lock permits tiller to be used as a handle during transport

Colours:



Silver

Options:

- Cane/crutch holder
- Oxygen tank holder
- Cup holder
- Rear basket
- Walker holder
- Upgrade to 40 amp batteries

The information contained herein is correct at the time of publication; due to the manufacturer's commitment to constant improvement and development, they reserve the right to alter specifications without prior notice.

**Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement.*