

Lightweight active wheelchair

Available in 4 seat depths and 2 frame lengths
Foldable aluminum lightweight frame

G6
"Active"

Backrest, fitted with 8 adjustable straps.
Angle adjustable backrest (one time adjustment), 90 to 105 degrees.
Height adjustable, 42½, 45 and 47½ cm.
Foldable aluminum crossbar.

Armpads made of comfortable polyurethane.
Short armrests, height adjustable and removable.

Seat cushion 5 cm, with non slip material.
Adjustable seat upholstery.

Footrests detachable, swing away, swing in.
Footplates height adjustable.

Tie down points illustrated for transportation.

Castors 6" x 1¼" (PU) with new design front forks.
Angle adjustable front castors.

Footplates angle adjustable 90 - 105 degrees with adjustable nylon heel loops. Footplates depth adjustable.

Height and angle adjustable push handles.

Backrest tension bar, foldable offering extra stability for the backrest.

Depth and angle adjustable aluminum brakes with extra comfy levers.

Wheelbase adjustments, 6 positions horizontal and vertical.

Quick release detachable lightweight rear wheel, with high pressure tyre.

Anti-tip system, height adjustable, length adjustable.
Quick release removable.

Seat height adjustable front, standard height 50 cm (with 6 options).



Mobility solutions for independent living



Available in various frame colours.
Frame colour option: lime green



Available in various frame colours.
Frame colour option: scuderia red.



Swing away and depth adjustable footplates.



Flip backward, height adjustable and detachable armrests, (optional detachable clothes protectors)

Standard specifications

Seat width: 40, 42½, 45 and 50 cm
Seat depth: 40, 43, 46 and 49 cm
Seat height: 43, 45, 47½, 50, 51½ and 53 cm
Backrest height: 42½, 45 and 47½ cm (adjustable)
Total width: Seat width + 17 cm
Total length: > 100 cm
Total height: > 95 cm
Width folded: 31 cm
Armrest height: 19-35 cm adjustable

Front castor size: 6" x 1¼" (other sizes available)
Rear wheel (sp): 24" x 1" (other sizes available)

Total weight (from): 14.9 kg (depending on the model)
Weight (transport): 9.2 kg
Max. user weight: 130 kg (seat width 50, 150 kg)

Frame colour available in:



Product complies with crash test ISO 7176-19:2001 and EN12183



All rights reserved. Copyright 2008© Van Os Medical B.V.®



Van Os Medical UK Ltd
Corunna House
42-44 Ousegate
Selby
YO8 4NH

Tel.: +44 (0)1757 701177
Fax: +44 (0)1757 706011

sales@vanosmedical.com